

Report No.: 56.03711 NOVAL Downlight

Test Time: 2023-07-04 20:06

Luminaire Property

Luminaire Category: Bridgelux V4HD 3000K CRI90

Voltage: 218.7 V

Current: 0.055 A

Power: 6.40 W

Power Factor: 0.532

Photometric Results

CIE Class: Direct

Measurement Flux: 348.9 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H16.6

Vertical Diffuse Angle(50%): V16.6

Luminaire Efficacy Rating (LER): 55

Max. Intensity: 2793.12 cd

Total Rated Lamp Lumens: 348.9 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 2735.71 cd

Pos of Max. Intensity: H0 V5

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G5

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 2793 cd

(10%): 279 cd	(16%): 447 cd
(25%): 698 cd	(40%): 1117 cd
(63%): 1760 cd	(100%): 2793 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m		Max Lux(100%): 28 lx	
(1%):	0 lx	(2%):	1 lx
(5%):	1 lx	(10%):	3 lx
(20%):	6 lx	(50%):	14 lx
(100%):	28 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance




Vertical IsoLux Plot



Lowest(m): 1m Highest(m): 11 Max Lux: 2736

(1%): 27 lx	(2%): 55 lx
(5%): 137 lx	(10%): 274 lx
(20%): 547 lx	(50%): 1368 lx
(100%): 2736 lx	

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Zonal Lumen

[illegible]

Inspector:

Candlepower Table

Unit: cd

[illegible]

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector: