

Report No.:56.05517 Recessed Downlight Test Time: 2023-06-30 21:26

Luminaire Property

Luminaire Category: Citizen 1204 3000K CRI90

Luminaire Description: FOS 65 36D

Voltage: 220.1 V

Power: 24.10 W

Lamp Description: Citizen 1204 3000K CRI90

Current: 0.113 A

Power Factor: 0.967

Photometric Results

CIE Class: Direct

Measurement Flux: 1716.9 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H32.1

Vertical Diffuse Angle(50%): V32.1

Luminaire Efficacy Rating (LER): 71

Max. Intensity: 4934.42 cd

Total Rated Lamp Lumens: 1716.9 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 4934.42 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 4934 cd

(10%): 493 cd	(16%): 790 cd
(25%): 1234 cd	(40%): 1974 cd
(63%): 3109 cd	(100%): 4934 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m		Max Lux(100%): 49 lx	
(1%):	0 lx	(2%):	1 lx
(5%):	2 lx	(10%):	5 lx
(20%):	10 lx	(50%):	25 lx
(100%):	49 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 4934

(1%): 49 lx	(2%): 99 lx
(5%): 247 lx	(10%): 493 lx
(20%): 987 lx	(50%): 2467 lx
(100%): 4934 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Zonal Lumen

[illegible]

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

Candlepower Table

Unit: cd

[illegible]

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector: