

$57.05511\,\text{SILO}$ Recessed Downlight Trimless



	350°	60°	3593cd	60°
Light Distribution	SILO Recessed Downlight	Light Beam Talbe		
Colour Temperature	2700/3000/3500/4000K	h(m)	E(lx)	D(m)
Colour Rendition Index	CRI 90	1.0	2270	24°
Optics	LENS	1.0 2.0	3279 819	0.42 0.85
Beam Angle	18D/24D/29D	3.0	364	1.27
Cut Out	55mm	4.0	204	1.70
Connected Load	10W	5.0	131	2.12
Luminous Flux Of The Luminaire	677lm	Star hotel rooms, aisles, villas, high-end private		
Luminaire Efficacy	74m/W		staurants and cial spaces	d other
Colour Deviation	SDCM<5	(such as	(such as furniture stores,	
Light Source	LED	ceramic and sanitary ware chain shops, brand chain		
LED Type	СОВ	shops and other commercial atmosphere lighting applications)		are lighting
Dimming Method	Triac/1-10V/ Dali			
Cover Material	Aluminum			
Body Material	Aluminum			
IP Rating	IP20			
Housing Colour	Sandy White/ Sandy Black			
Weight	0.5Kg			
Technical Region	220-240V 50/60Hz			